



Quality You Can Believe In!



AVENGER SERIES

S SERIES

UAK SERIES

OIL-MINDER

CONTROLS

ACCESSORIES

MODELS SW-200, SW-200/1, SW-300, and SW-500

Channel Impeller Sewage Pump

Open channel impeller in volute for handling abrasive liquids or foreign matters without clogging. High efficiency design..

Output:

- 2 HP & 3 HP

Construction

- Completely watertight cable entry sealed with epoxy resin. The individual cores are embedded in cast resin to prevent water tracking.
- Durable cast iron outer case with amply dimensioned colling ribs achieves superior heat dissipation.



Motor:

- Oil-free hermetically sealed, with built-in thermal overload protector.
- 1 & 3 phase, 2 pole, 60 Hz 3450 rpm, Insulation Class F=155°C, Protection type IP68. (50 Hz version available upon request.)

Channel Impeller:

- The cast iron impeller has an open channel design for handling 3" diameter abrasive liquids or solid foreign matter without clogging. Channel impeller design provides maximum efficiency..



new!

**Avenger SSD
200
2 HP
dewatering
pump for utility
vaults, mining,
construction
and other
applications**



**Avenger SS
Series
Constructed of
316 stainless
steel. Models
up to 7.5 H.P.**

Applications:

- Draining from buildings and sanitary facilities.
- Treatment process for plant and industrial wastewater..
- Raw water transfer station at treatment plants..

General & Electrical Specifications:

	SW-200	SW-200/1	SW-300	SW-500
HP	2	2	3	5
Voltage	230 / 460	1ph / 230	230 / 460	460
Discharge Size	3"	3"	3"	3"
Maximum Head (ft.)	52'	52'	63'	79'
Maximum Flow (gpm)	211	211	238	317
Weight (lbs.)	90	90	106	121

[HOME](#) | [PUMPS](#) | [CONTROLS](#) | [ACCESSORIES](#) | [ENVIRONMENTAL](#) | [CONTACT](#) | [LINKS](#)

STANCOR, Inc., 515 Fan Hill Rd., Monroe, CT 06468

Phone: (203) 268-7513

Fax: (203)268-7958

stancor@stancorpumps.com

© Copyright 2004 Stancor, Inc. All Rights Reserved.