

**TECHNICAL DATA****AVENGER SERIES****AHS-10HH**

STANCOR

Dwg: DS-A05-001 Rev: 2 Date: 01/16

MOTOR SPECIFICATIONS

Motor Design	Induction
Motor Type	Enclosed submersible
Insulation Class	Class B
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	120° C ± 5° C
Service Factor	1.3
Voltage Tolerance	± 10% from nominal

**MOTOR DATA, 60Hz**

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
AHS-10HH	1	1.0	115	12	60.0	H	0.987	0.689	2/3450
	1	1.0	230	6.0	30.0	H	0.98	0.69	2/3450
	3	1.0	230	3.4	17.0	H	0.890	0.73	2/3450
	3	1.0	460	2.0	10.0	J	0.893	0.741	2/3450
	3	1.0	575	1.7	8.5	K	0.891	0.753	2/3450

MATERIALS OF CONSTRUCTION

Upper Motor Lid	Aluminum (ADC 12)
Motor Housing	Aluminum (ADC 12)
Oil Chamber / Volute	Cast Iron (FC20)
Strainer	PVC
External Hardware	AISI 304 Stainless Steel
O-Rings	NBR
Motor Shaft	Stainless Steel (SUS 410)
Upper Bearing	Single ball bearing, double sealed.
Lower Bearing(s)	Single ball bearing, double sealed.
Upper Shaft Seal	CA/CE (carbon/ceramic)
Lower Shaft Seal	SIC/SIC (silicon carbide/silicon carbide)
Impeller	Cast Iron (FC15)

DIMENSIONS, WEIGHT, AND MISC.

Pump weight single phase	33lbs (14kg)
Pump weight three phase	33lbs (14kg)
Maximum submergence	33 feet (10m)
Discharge size, standard	2 inch NPT female vertical
Maximum temp. of pumped fluid	104°F (40°C)

CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE	LENGTH	OUTER JACKET
AHS-10HH	1Ø-115V	SJTW 14/3	33 feet (10m)	NBR
	1Ø-230V	SJTW 16/3	33 feet (10m)	NBR
	3Ø-230V	STOW 16/4	33 feet (10m)	NBR
	3Ø-460V	STOW 16/4	33 feet (10m)	NBR
	3Ø-575V	STOW 16/4	33 feet (10m)	NBR

Power cable suitable for all standard voltages listed in "MOTOR DATA" section.

Specifications subject to change without notice