

**TECHNICAL DATA****AVENGER SERIES****SEW-150**

STANCOR

Dwg: DS-A02-019 Rev: 2 Date: 01/16

MOTOR SPECIFICATIONS

Motor Design	NEMA design B, squirrel cage induction
Motor Type	Enclosed submersible
Insulation Class	Class E
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	120° C ± 5° C
Service Factor	1.3
Voltage Tolerance	± 10% from nominal

**MOTOR DATA, 60Hz**

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
SEW-150	1	1.5	115	17.6	88.0	H	0.95	0.69	2/3450
	1	1.5	230	9.7	48.5	J	0.93	0.69	2/3450
	3	1.5	230	5.5	27.5	J	0.93	0.75	2/3450
	3	1.5	460	2.8	14.0	J	0.91	0.75	2/3450
	3	1.5	575	2.5	12.5	K	0.90	0.75	2/3450

MATERIALS OF CONSTRUCTION

Upper Motor Lid	Cast Iron ASTM A48 Class 30
Motor Housing	AISI 304 Stainless Steel
Oil Chamber	Cast Iron ASTM A48 Class 30
Volute	Cast Iron ASTM A48 Class 30
External Hardware	AISI 304 Stainless Steel
O-Rings	NBR
Motor Shaft	AISI 410 Stainless Steel
Upper Bearing	Single row Sealed
Lower Bearing(s)	Single row Sealed
Upper Shaft Seal	Carbon/Ceramic
Lower Shaft Seal	SiC/SiC
Impeller	Cast Iron ASTM A48 Class 30

DIMENSIONS, WEIGHT, AND MISC.

Pump weight single phase	55lbs (25kg)
Pump weight three phase	55lbs (25kg)
Maximum submergence	33 feet (10m)
Discharge size, standard	2" NPT female vertical
Maximum temp. of pumped fluid	104°F (40°C)

CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE	LENGTH	OUTER JACKET
SEW-150	1Ø-115V	SJTOW 12/3	33feet (10m)	NBR
	1Ø-230V	SJTOW 14/3	33feet (10m)	NBR
	3Ø-230V	STOW 16/4	33feet (10m)	NBR
	3Ø-460V	STOW 16/4	33feet (10m)	NBR
	3Ø-575V	STOW 16/4	33feet (10m)	NBR

Power cable suitable for all standard voltages listed in "MOTOR DATA" section.

Specifications subject to change without notice

Stancor, Inc. 515 Fan Hill Road, Monroe, CT 06468

Tel: 203-268-7513

Fax : 203-268-7958

www.stancorpumps.com