

**TECHNICAL DATA****AVENGER SERIES****SL-75**

STANCOR

Dwg: DS-A12-001 Rev: 4 Date: 07/17

MOTOR SPECIFICATIONS

Motor Design	Induction
Motor Type	Enclosed submersible
Insulation Class	Class B
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	120° C ± 5° C
Service Factor	1.0
Voltage Tolerance	± 10% from nominal

**MOTOR DATA, 60Hz**

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
SL-75	1	0.75	115	7.0	35.0	F	0.99	0.62	2/3450
	1	0.75	208	3.9	19.5	F	0.99	0.61	2/3450
	1	0.75	230	3.5	17.5	F	0.99	0.61	2/3450
	3	0.75	208	2.0	10.0	E	0.81	0.65	2/3450
	3	0.75	230	1.8	9.0	E	0.81	0.65	2/3450
	3	0.75	460	1.0	5.0	F	0.84	0.66	2/3450
	3	0.75	575	1.0	5.0	H	0.81	0.67	2/3450

MATERIALS OF CONSTRUCTION

Discharge Connection	Cast Iron (FC15)
Motor Housing	AISI 304 Stainless Steel
Oil Chamber	Aluminum (ADC 12)
Volute	Cast Iron (FC20)
External Hardware	AISI 304 Stainless Steel
O-Rings	NBR
Motor Shaft	Stainless Steel(410)
Upper Bearing	Single row, doubled sealed
Lower Bearing(s)	Single row, doubled sealed
Upper Shaft Seal	CA/CE (carbon/ceramic)
Lower Shaft Seal	SIC/SIC (silicon carbide/silicon carbide)
Impeller	Hytrek (steel coated with thermoplastic polyester elastomer)

DIMENSIONS, WEIGHT, AND MISC.

Pump weight single phase	24lbs (11kg)
Pump weight three phase	24lbs (11kg)
Maximum submergence	30 feet (9m)
Discharge size, standard	2 inch NPT female vertical
Maximum temp. of pumped fluid	104°F (40°C)
Inlet Opening	2 mm

CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE	LENGTH	OUTER JACKET
SL-75	1Ø-115V	SJTW 16/3	50 feet (15m)	NBR
	1Ø-208V	SJTW 16/3	50 feet (15m)	NBR
	1Ø-230V	SJTW 16/3	50 feet (15m)	NBR
	3Ø-208V	STOW 16/4	50 feet (15m)	NBR
	3Ø-230V	STOW 16/4	50 feet (15m)	NBR
	3Ø-460V	STOW 16/4	50 feet (15m)	NBR
	3Ø-575V	STOW 16/4	50 feet (15m)	NBR

Power cable suitable for all standard voltages listed in "MOTOR DATA" section.

Specifications subject to change without notice

Specifications subject to change without notice

Stancor, Inc. 515 Fan Hill Road, Monroe, CT 06468

Tel: 203-268-7513

Fax : 203-268-7958

www.stancorpumps.com