

**TECHNICAL DATA****AVENGER SERIES****SSS-75**

STANCOR

Dwg: DS-A14-001 Rev: 2 Date: 01/16

MOTOR SPECIFICATIONS

Motor Design	Induction
Motor Type	Enclosed submersible
Insulation Class	Class B
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	120° C ± 5° C
Service Factor	1.3
Voltage Tolerance	± 10% from nominal

**MOTOR DATA, 60Hz**

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
SSS-75	1	0.5	115	7	35	K	1.00	0.624	2/3450
	1	0.5	230	3.5	17.5	K	1.00	0.621	2/3450
	3	0.5	230	1.8	9	J	0.82	0.660	2/3450
	3	0.5	460	1	5	J	0.83	0.663	2/3450
	3	0.5	575	1	5	L	0.81	0.667	2/3450

MATERIALS OF CONSTRUCTION

Discharge Connection	AISI 304 Stainless Steel
Motor Housing	AISI 304 Stainless Steel
Oil Chamber	AISI 304 Stainless Steel
Volute	AISI 304 Stainless Steel
External Hardware	AISI 304 Stainless Steel
O-Rings	NBR
Motor Shaft	Stainless Steel-410
Upper Bearing	Single row, doubled sealed
Lower Bearing(s)	Single row, doubled sealed
Upper Shaft Seal	CA/CE
Lower Shaft Seal	CA/CE
Impeller	AISI 304 Stainless Steel

DIMENSIONS, WEIGHT, AND MISC.

Pump weight single phase	26lbs (12kg)
Pump weight three phase	26lbs (12kg)
Maximum submergence	33 feet (10m)
Discharge size, standard	2 inch NPT female vertical
Maximum temp. of pumped fluid	104°F (40°C)

CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE	LENGTH	OUTER JACKET
SSS-75	1Ø-115V	SJTW 16/3	50feet (15m)	NBR
	1Ø-230V	SJTW 16/3	50feet (15m)	NBR
	3Ø-230V	STOW 16/4	50feet (15m)	NBR
	3Ø-460V	STOW 16/4	50feet (15m)	NBR
	3Ø-575V	STOW 16/4	50feet (15m)	NBR

Power cable suitable for all standard voltages listed in "MOTOR DATA" section.

Specifications subject to change without notice