



# TECHNICAL DATA

# Mine Dewatering Pumps SX2000 HH &HV

STANCOR

Dwg: DS-A16-052 Rev: 3 Date: 11/16

## MOTOR SPECIFICATIONS

Motor Design	NEMA design B, squirrel cage induction, air filled
Motor Type	Enclosed submersible, IP 68
Maximum submergence	65 feet (20m)
Insulation Class	Class F, rated at 155° C
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	130° C ± 5° C
Service Factor	1.15
Max. Liquid Temperature	104°F (40°C)
Voltage Tolerance	± 10% from nominal
MSHA Approval	2G-3142A-0



## MOTOR DATA, 60Hz

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
SX-2000	3	18	230	49	242.3	F	0.87	0.87	2/3450
			460	24.5	121.1	F	0.87	0.87	2/3450
			575	17.25	84.3	E	0.87	0.87	2/3450
			950	13	75	H	0.87	0.87	2/3450

## MATERIALS OF CONSTRUCTION

Upper Motor Lid	356-T6 Aluminum
Motor Housing	356-T6 Aluminum
Oil Chamber	AISI 304 Stainless Steel
Volute	356-T6 Aluminum - Rubber Lined
External Hardware	AISI 304 Stainless Steel
O-Rings	NBR
Motor Shaft	AISI 416 Stainless Steel
Upper Bearing	Deep groove ball bearing, double sealed
Lower Bearing	Double row angular contact ball bearing, double shielded
Upper Shaft Seal	Carbon/Ceramic
Lower Shaft Seal	SiC/SiC
Impeller HH	AISI 316 Stainless Steel
Impeller HV	17-4PH Stainless Steel

## DIMENSIONS, WEIGHT, AND MISC.

Pump weight (without cable)	282 lbs (127.9 kg)
Discharge size, HH	4 inch NPT male vertical
Discharge size, HV	6 inch NPT male vertical

## CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE *	LENGTH *	OUTER JACKET
SX2000	3Ø-230V	8/3, 6/3, 4/3 G-GC	Per MSHA Approval	CPE, Heavy Duty
	3Ø-460V	8/3, 6/3, 4/3 G-GC	Per MSHA Approval	CPE, Heavy Duty
	3Ø-575V	8/3, 6/3, 4/3 G-GC	Per MSHA Approval	CPE, Heavy Duty
	3Ø-950V	6/3, 4/3 SHD-GC	Per MSHA Approval	CPE, Heavy Duty

\* Cable size and length per MSHA approval.



Specifications subject to change without notice

Specifications subject to change without notice

Stancor, L.P. 515 Fan Hill Road, Monroe, CT 06468

Tel: 203-268-7513

Fax : 203-268-7958

[www.stancorpumps.com](http://www.stancorpumps.com)