



TECHNICAL DATA

Well Casing Pumps WCP-400 HH

STANCOR

Dwg: DS-A28-009

Rev:

Date: 2/18

MOTOR SPECIFICATIONS

Motor Design	Induction
Motor Type	Enclosed submersible
Insulation Class	Class F
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	120° C ± 5° C
Service Factor	1.15
Voltage Tolerance	± 10% from nominal



MOTOR DATA, 60Hz

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
WCP 400 HH	3	4	230	12.2	61	G	0.78	0.82	2/3450
	3	4	460	6.3	31.5	G	0.76	0.83	2/3450
	3	4	575	5.1	25.5	H	0.77	0.81	2/3450

MATERIALS OF CONSTRUCTION

Upper Motor Lid	Cast iron
Motor Housing	AISI 304 Stainless Steel
Oil Chamber	Cast iron
Volute	Cast iron
External Hardware	AISI 304 Stainless Steel
O-Rings	NBR
Motor Shaft	AISI Stainless Steel 410 (in pumped media)
Upper Bearing	C3 Shielded ball bearings
Lower Bearing(s)	C3 Shielded ball bearings
Upper Shaft Seal	CA/CE (carbon/ceramic)
Lower Shaft Seal	SIC/SIC (silicon carbide/silicon carbide)
Impeller	High Chrome Iron

DIMENSIONS, WEIGHT, AND MISC.

Pump weight single phase	99lbs (45kg)
Pump weight three phase	99lbs (45kg)
Maximum submergence	66 feet (20m)
Discharge size, standard	2-inch NPT male vertical
Maximum temp. of pumped fluid	104°F (40°C)
Free Passage size	0.3" (7mm)

CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE	LENGTH	OUTER JACKET
WCP 400 HH	3Ø-230V	8/3 G-GC	100 feet (30.48m)	PVC
	3Ø-460V	8/3 G-GC	100 feet (30.48m)	PVC
	3Ø-575V	8/3 G-GC	100 feet (30.48m)	PVC

Power cable suitable for all standard voltages listed in "MOTOR DATA" section.

Specifications subject to change without notice

Stancor, LP. 515 Fan Hill Road, Monroe, CT 06468
www.stancorpumps.com

Tel: 203-268-7513

Fax : 203-268-7958